




SERIES 27/FS27


SEAL WELD CLASS 1500

BALL VALVE

3600 CWP Series FS27 316 STAINLESS STEEL - ASTM A351 CF8M CARBON STEEL - ASTM A216 WCB **FIRE SAFE** NACE MR0175 (13)SATURATED STEAM (WSP) 250 PSI AT 406°F (PEEK SEATS) ANTI STATIC DEVICE **BLOWOUT PROOF STEM** LIVE LOADED STEM LOCKABLE HANDLE FULLY COMPLIANT TO API 608 ANTI-STATIC DESIGN (14) 8 7 12 0 9 0 8 (4 (4A) (4A)(1) (5) 3 PARTS AND MATERIAL 5 6 2

PART NO.	PART NAME	QTY.	MATERIAL
1	Body	1	Carbon Steel ASTM A216 WCB 316 Stainless Steel ASTM A351 CF8M
2	End Piece	1	Carbon Steel ASTM A216 WCB 316 Stainless Steel ASTM A351 CF8M
3	Ball	1	316 Stainless Steel ASTM A351 CF8M
4	Stem	1	316 Stainless Steel
4A	Anti-Static Ball	2	300 Series Stainless Steel Hard Drawn Stainless Steel
5	Seat	2	PEEK / Delrin
6	Body Seal	1	Graphite
7	Thrust Bearing	1	PEEK
8	Stem Packing	1 Set	Graphite
9	Packing Nut	1	304 Stainless Steel
10	Travel Stopper	1	304 Stainless Steel
11	Screw	2	304 Stainless Steel
12	Handle	1	Carbon Steel ASTM A216 WCB
13	Handle Sleeve	1	PVC
14	Flange Nut	1	304 Stainless Steel





DIMENSIONS (INCHES)


SIZE	А	В	С	D	E	F	G	Н	I	ISO5211
1/4″	2.99	2.43	5.12	0.25	1/4-20UNC	1.42	0.20	0.31	NPT	F03
3/8″	2.99	2.43	5.12	0.25	1/4-20UNC	1.42	0.20	0.31	NPT	F03
1/2″	4.00	2.43	5.12	0.50	1/4-20UNC	1.42	0.20	0.31	NPT	F03
3/4″	4.25	2.99	5.71	0.75	1/4-20UNC	1.65	0.28	0.44	NPT	F04
1″	4.25	2.99	5.71	0.75	1/4-20UNC	1.65	0.28	0.44	NPT	F04
1″	4.50	3.85	10.00	1.00	1/4-20UNC	1.97	0.35	0.56	NPT	F05
1-1/2″	5.29	4.66	13.78	1.50	5/16-18UNC	2.76	0.39	0.62	NPT	F07
2″	6.25	4.66	13.78	1.50	5/16-18UNC	2.76	0.39	0.62	NPT	F07

APPLICABLE STANDARDS

BASIC DESIGN	ASTM B16.34 CLASS 1500
SHELL & SEATS PRESSURE TEST	ASME B16.34
SOCKET WELD ENDS	ASME B16.11
THREADED ENDS	ASME B16.11
FIRE SAFE	API 607 6th EDITION (Fire Safe Only)

SIZE	CV (GPM)	WEIGHT (LBS)
1/4″	6.1	1.54
3/8″	6.1	1.50
1/2″	26	1.72
3/4″	61	3.09
1″	51	2.82
1″	114	4.45
1-1/2″	272	11.73
2″	229	12.92

PRESSURE-TEMPERATURE RATINGS SERIES FS27



HOW TO ORDER

